

FORKLIFTS
AUSTRALIA



UN FORKLIFT

NL Series Lithium Forklift Truck

2.0-3.5Ton Lithium Battery Counterbalance Forklift





2.0T FORKLIFT
3m Duplex Mast, Pneumatic Tyres



2.5T FORKLIFT
3m Duplex Mast, Pneumatic Tyres



3.0T FORKLIFT
3m Duplex Mast, Pneumatic Tyres



3.5T FORKLIFT
3m Duplex Mast, Pneumatic Tyres

ADDITIONAL OPTIONS AVAILABLE:

Triplex Mast, Solid and Non-marking Tyres, Fork Positioner

Market leading engines ensure superior performance, durability and excellent fuel efficiency. All diesel forklifts have Mitsubishi or Isuzu engines. The LPG and gasoline forklifts utilise Nissan engines.



THE FORKLIFTS AUSTRALIA DIFFERENCE

Forklifts Australia is committed to delivering professional industry advice, quality equipment and outstanding service.

They are the exclusive distributor of UN Forklifts, offering a full range of LPG, Diesel and Rough Terrain forklifts to suit a range of applications. UN Forklifts are one of the largest and most experienced material handling equipment manufacturers in the world that offer advanced technology and robust machinery.

Forklifts Australia also offers equipment from other market-leading brands including Royal, Merlo, JLG, Genie, Manitou and Yale.

Not only can we provide market leading forklifts but we can also provide quality servicing and repairs throughout Australia. Our expert team of 24 / 7 mobile service technicians can service and repair an extensive range of forklifts, including LPG, Diesel and electric forklifts giving you peace of mind that you'll be back on site soon.

Forklifts Australia is the leading supplier of forklifts in the Australian market, and has been in operation for over 10 years. We pride ourselves on offering superior customer service and are located across Australia with branches in Perth, Sydney, Melbourne, Adelaide, Darwin and Brisbane.

PERFECT FOR THESE INDUSTRIES



Freight



Store
Distribution



Manufacturing



Farming &
Landscape



Packing



Third Party
Logistics






N
series

NL Series Lithium Battery Counterbalance Forklift

CAPACITY 2,000 TO 3,500KG

The NL series new lithium battery forklift adopts UN internal combustion forklift's design with the strong chassis, frame, counterweight and mast. The power structure is designed to adopt UN electric forklift's concept, which use full AC system, Italy imported ZAPI controller, BMS control system and high quality lithium battery. This combination of IC forklift and electric forklift makes an ideal solution to reach customers' satisfaction on cost saving and environmental friendly.



ADVANTAGES OF LITHIUM BATTERY TECHNOLOGY

STRONG AND DURABLE CHASSIS

Using the IC truck structures, which has been tested by the market for more than 20 years.





LONG TERM PERFORMANCE

The battery can be charged and discharged 4000 times. With 5 years guarantee on lithium battery gives customers great satisfaction and long time life cycle.



ECO-FRIENDLY

Using low-carbon, clean, and environmental friendly lithium battery. Lower noise, zero emission, and less vibration.



LOWER TOTAL OWNERSHIP COST (TOC)

The purchase price is similar to a regular IC forklift . No fuel consumption cost , no maintenance fee for air filter, oil filter or engine oil changes compare to a regular IC forklift.




MULTI-SCENARIO USAGE

Adopting the IC forklift structures enable to operate indoors and outdoors, with great waterproof and dustproof performance.



FAST CHARGING (GUN CHARGING OPTIONAL)

Fully charge only needs 2 hours, and it can be charged at any time during the day to ensure multiple shifts.



COMFORT AND ERGONOMICS

Owing to the low center of gravity and good stability, the driver feels comfortable during turning. Bigger leg space than standard Li-ion forklifts.



2.0-2.5 TON MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Mast Name	Max Fork Height (mm)	Load Capacity (kg)				Overall Height (mm)			Free Lift (mm)		Tilt Angle (Single)	Tilt Angle (Double)			
			FB20	FB20 (Double)	FB25	FB25 (Double)	Lowered	Extended		Without Backrest	Without Backrest					
								Without Backrest	With Backrest							
											2.0t / 2.5t		2.0t / 2.5.0t			
Wide View Mast	M300	3000	2000	2000	2500	2500	2055	3580	4070	100	100	6-12	6-12			
	M330	3300	2000	2000	2500	2500	2205	3880	4370	100	100	6-12	6-12			
	M400	4000	2000	2000	2450	2450	2605	4580	5070	100	100	6-6	*6-12			
	M450	4500	1800	*1900	2000	*2400	2855	5080	5570	100	100	6-6	*6-12			
	M470	4700	1450	*1850	1750	*2050	2955	5280	5770	100	100	6-6	*6-12			
	M500	5000	1300	*1700	1600	*2100	3155	5580	6070	100	100	6-6	*6-6			
	M550	5500	1100	*1500	1350	*1700	3405	6080	6570	100	100	3-6	*3-6			
2-Stage Full Free View Mast	FM300	3000	2000	2000	2500	2500	2070	3605	4068	1470	1007	6-12	6-12			
	FM370	3700	2000	2000	2500	2500	2420	4255	4718	1800	1357	6-6	6-6			
	FM400	4000	2000	2000	2500	2500	2670	4605	5068	2000	1607	6-6	*6-12			
3-Stage Full Free View Mast	TFM450	4500	1700	*1800	2000	*2300	2095	5107	5570	1498	1035	6-6	*6-6			
	TFM470	4700	1600	*1750	1900	*2200	2145	5307	5770	1548	1085	6-6	*6-6			
	TFM500	5000	1400	*1600	1500	*2000	2245	5607	6070	1648	1185	6-6	*6-6			
	TFM550	5500	1100	*1500	1200	*1800	2445	6107	6570	1800	1385	3-6	*3-6			
	TFM600	6000	800	*1400	850	*1600	2645	6607	7070	2000	1585	3-6	*3-6			
	TFM650	6500	500	*1100	550	*1200	2895	7107	7570	2200	1835	3-6	*3-6			
	TFM700	7000	100	*700	150	*800	3095	7607	8070	2300	2035	3-6	*3-6			

Note: With Separated Side shifter, load capacity subtract 200Kg, With Integrated side shifter, load capacity subtract 50Kg.


2. * (Asterisk) is for double front wheels model.

3.0-3.5 TON MAST SPECIFICATIONS & RATED CAPACITIES

Mast Type	Mast Name	Max Fork Height (mm)	Load Capacity (kg)			Overall Height (mm)			Free Lift (mm)		Tilt Angle (Single)	Tilt Angle (Double)				
			FB30	FB30 (Double)	FB35	Lowered	Extended		Without Backrest	Without Backrest						
							Without Backrest	With Backrest								
											3.0t / 3.5t		3.0t / 3.5.0t			
Wide View Mast	M300	3000	2000	2000	2500	2070	3595	4070	100	100	6-12	6-12				
	M330	3300	2000	2000	2500	2220	3895	4370	100	100	6-12	6-12				
	M370	4000	2000	2000	2450	2420	4295	4770	100	100	6-6	6-6				
	M400	4500	1800	*1900	2000	2620	4595	5070	100	100	6-6	*6-12				
	M450	4700	1450	*1850	1750	2870	5095	5570	100	100	6-6	*6-12				
	M470	5000	1300	*1700	1600	2970	5295	5770	100	100	6-6	*6-12				
	M500	5500	1100	*1500	1350	3170	5595	6070	100	100	6-6	*6-6				
	M550	6000	950	*1300	1050	3420	6095	6570	100	100	3-6	*3-6				
2-Stage Full Free View Mast	FM300	3000	3000	3000	3500	2070	3590	4065	1382	907	6-12	6-12				
	FM330	3300	3000	3000	3500	2220	3940	4415	1532	1057	6-12	6-12				
	FM370	3700	3000	3000	3500	2420	4240	4715	1732	1257	6-6	6-6				
	FM400	4000	3000	3000	3250	2670	4590	5065	1982	1507	6-6	*6-12				
3-Stage Full Free View Mast	TFM450	4500	2600	*2800	2800	2110	5200	5675	1422	947	6-6	*6-6				
	TFM470	4700	2400	*2700	2500	2160	5400	5875	1472	997	6-6	*6-6				
	TFM500	5000	2100	*2400	2300	2260	5700	6175	1572	1097	6-6	*6-6				
	TFM550	5500	1650	*2250	1800	2460	6200	6675	1772	1297	3-6	*3-6				
	TFM600	6000	1200	*2100	1300	2660	6700	7175	1972	1497	3-6	*3-6				
	TFM650	6500	950	*1700	1050	2910	7200	7675	2200	1747	3-6	*3-6				
	TFM700	7000	650	*1400	750	3110	7700	8175	2300	1947	3-6	*3-6				

Note: With Separated Side shifter, load capacity subtract 200Kg, With Integrated side shifter, load capacity subtract 50Kg

2. * (Asterisk) is for double front wheels model.




NL Series Lithium Battery

2.0T - 3.5T Counterbalance Forklift

MAIN SPECIFICATIONS (STANDARD PERFORMANCE)

General	1	Model		FB20-YNLZ2	FB25-YNLZ2	FB30-YNLZ2	FB35-YNLZ2
	2	Rated Load Capacity	Q(kg)	2000	2500	3000	3500
	3	Load Centre	C(mm)	500	500	500	500
Characteristic & Dimension	4	Rated Lift Height	H3(mm)	3000	3000	3000	3000
	5	Free Lift Height	H2(mm)	100	100	100	100
	6	Fork Size (LxWxT)	mm	1070x120x40	1070x120x40	1070x125x45	1070x125x50
	7	Mast Tilt Angle (F/R, α°/β°)	deg	6°/12°	6°/12°	6°/12°	6°/12°
	8	Fork Overhang (Wheel Center to Fork Face)	X1(mm)	479	479	484	484
	9	Rear Overhang	X2(mm)	520	520	595	635
	10	Ground Clearance (Bottom of Mast)	H7(mm)	130	130	145	145
	11	Length to Face of Fork (Without Fork)	L1(mm)	2660	2660	2700	2775
	12	Overall Width	B1(mm)	1150	1150	1225	1225
	13	Mast Lowered Height	H1(mm)	2055	2055	2070	2070
	14	Mast Extended Height (With Backrest)	H4(mm)	4070	4070	4070	4070
	15	Overhead Guard Height	H5(mm)	2215	2215	2235	2235
	16	Turning Radius (Outside)	Wa(mm)	2365	2365	2425	2500
	17	Min.Aisle width for pallets	Ast(mm)	4120	4120	4180	4255
	Performance	18	Travel Speed (Full Load/No Load)	km/h	11/12	11/12	11/12
19		Lifting Speed (Full Load/No Load)	mm/sec	260/380	260/380	250/360	220/340
20		Lowering Speed (Full Load)	mm/sec	450	450	450	450
21		Max.Gradeability (Full Load)	%	15	15	12	12
Chassis	22	Tyre (Front x 2)	mm	7.00-12-12PR	7.00-12-12PR	28x9-15-12PR	28x9-15-12PR
	23	Tyre (Rear x 2)	mm	6.00-9-10PR	6.00-9-10PR	6.50-10-10PR	6.50-10-10PR
	24	Front Tread	B2(mm)	970	970	1000	1000
	25	Rear Tread	B3(mm)	980	980	980	980
	26	Wheelbase	Y(mm)	1650	1650	1700	1700
Weight	27	Total Weight	kg	3385	3605	4460	4775
	28	Front Axle Weight Distribution (No Load/Full Load)	kg	1354/4846	1442/5494	1784/6714	1910/6997
	29	Rear Axle Weight Distribution (No Load/Full Load)	kg	2031/538	2163/610	2676/746	2865/777
Power & Transmission	30	Battery	V/Ah	80V/150AH option 220AH option 350AH	80V/175AH option 270AH option 350AH	80V/220AH option 270AH option 350AH	80V/270AH option 350AH
	31	Drive Motor	KW	10	10	10	10
	32	Lift Motor	KW	12	12	12	12
	33	Operating Pressure (For Attachments)	Mpa	17.5	17.5	17.5	17.5



HIRE

SALES

SERVICE

LEASE

TRANSPORT



WHY CHOOSE US?

- ✓ *Approaching 40 years experience*
- ✓ *Abundant various parts in stock*
- ✓ *Highly acknowledged for innovative design*
- ✓ *High efficiency and reliable quality*
- ✓ *Ergonomic design and humanistic service*
- ✓ *Quick after-sales service*
- ✓ *Customer orientation*

